

CHARACTERISTICS

Type:	Hydraulic Lift
Load:	180 kg up to 1600kg in "C" series and 1000 kg in "S" series.
Capacity:	4 to 13 persons
Speed:	0.63 and 0.52 m/s.
Travel:	Up to 27 m.
Stops:	10 stops
Entrances:	Single entrance, double 180° entrance, double 90° entrance and triple entrance.

CAR

Model:	MP CARevolution, C and D series
--------	---------------------------------

CAR DOORS

Type:	Automatic. Telescopic 2 panel.
Finish:	Stainless steel finish (X02).

LANDING DOORS

Type:	Automatic. Telescopic 2 panel.
Finish:	Epoxy RAL 7044
Fire resistance according to EN 81-58:	E120, EW60

CONTROL OPERATING PANEL

Model:	Column or FUSION with MP CARevolution
Finish:	Plastified steel (Optional: Stainless steel (X02))
Button:	Mechanical plastic polycarbonate fireproof button lit using LEDs (Optional: Mechanical stainless steel button with ring lighting)
Car indicator:	LCD and TFT display (Optional: 2-digit, 7-segment LED display)
Safety:	Emergency overhead lighting and telephone.

FLOOR OPERATING PANEL

Model:	P001, on door frame
Finish:	Stainless steel plate (X02)
Button:	Mechanical plastic polycarbonate fireproof button lit using LEDs. (Optional: Mechanical stainless steel button with ring lighting)
Engraving:	Black logo (laser)

CONTROLLER

Type:	MP Selective or Universal.
Location:	In machine room in series "C", free location of machine room. In cabinet in series "S". Epoxy finish. Recommended distance < 10 metres

ELECTRICAL INSTALLATION

Preassembled with "Plug & Play" connectors.

HYDRAULIC POWER UNIT

Electronic valve block MP greenvaive.
Automatic rescue.

BUFFERS

In polyurethane with metal pedestal included

COLD-DRAWN / MACHINED

Cold-drawn/ Machined
In accordance with ISO 7465

FIXINGS

Attachment supports and blocks for concrete walls.

POWER

Power voltage:	Three-phase 380 V (Optional: 380, 400v, 415v, three-phase, 220v single-phase)
Lighting:	220 V
Frequency:	50 Hz. (Optional:60Hz)